

# We BRIGHTEN Your BRANDS

## ChanneLED 5

### High output red solution

- Run 45 feet per SloanLED 60 W 12 VDC power supply
- SloanStretch expandable wire (+2 in) feature for optimum module placement
- Constant Current Technology (CCT)

## SPECIFICATIONS

**Part number** ..... 701269-R5-MB

**Dimensions L x W x H** ..... 4 in x 0.46 in x 0.45 in

**Viewing angle** ..... 120°

**LEDs per section** ..... 3

**Modules per foot** ..... 2

**Maximum coverage per row** ..... Can depth ..... ≥5 in  
Coverage ..... 7.5 in

**Operating temperature** ..... -40° C to +70° C

**Protection class** ..... IP66

**Special feature** ..... SloanStretch expandable wire (+2 in)

**Power per module** ..... 0.60 W

**Efficacy** ..... 30 lm/W

**Power capacity** ..... 90 modules per SloanLED 60 W 12 VDC power supply

**Fastening** ..... Peel-n-stick and mechanical

**Packaging** ..... 25 ft (50 modules) per tray, 5 trays per carton

**Color** ..... Red

**Lumens per module** ..... 18



SloanLED channel letter products are covered by US and foreign patents pending and covered by one or more of the following US patents issued: 6,932,495, 7,160,140, 7,241,031, 7,520,771, 7,931,386 and European Patent No. 1756471

SloanLED Headquarters  
5725 Olivias Park Drive • Ventura, California 93003  
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.  
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands  
+31 88 12 44 900 • Europe@SloanLED.com

**SloanLED.com**

© 2016 SloanLED RevB 2016-03-22

 **SloanLED**<sup>®</sup>  
Leaders in LED Technology