

We BRIGHTEN Your BRANDS



PosterBOX

Side illumination for shallow or narrow cabinets

- Easily illuminates double-sided cabinets with 100-150 mm depths
- Side mounted module
- FanFlare lens technology projects light in a fan pattern to evenly illuminate sign face
- Constant Current Technology (CCT)

SPECIFICATIONS

Part number	White (6500 K)	701946-CWPBM
	White (5000 K)	701946-NWPBM
Dimensions L x W x H	220 mm x 44 mm x 23 mm	
LEDs per module	3	
Light throw	1.2 m	
Module spacing	Cabinet depth	Center-to-center
	≤10 cm	30 cm
	>10 cm to ≤20 cm	45 cm
Operating temperature	-40° C to +70° C	
Location rating	IP66	
Special feature	FanFlare lens technology	
Power per module	6.7 W	

Efficacy	82 lm/W
Power capacity	8 modules per SloanLED 60 W 12 VDC power supply
Fastening	Peel-n-stick and mechanical
Packaging	10 modules and FlareShields™ per carton
Color temperatures	6500 K, 5000 K
Lumens per module	550
Accessory	FlareShield (401059) for shallower applications to eliminate hot spots



Green Signage 

PosterBOX™ is licensed under: Patents CN200680037992.9, DE202006020673.6, NL1030161, US6932495, and US7841733; and patent applications EP06812715.8 and NL2000273. Green Signage and PosterBOX™ are trademarks of Lux et Libertas BV. SloanLED, the S logo, and Leaders in LED Technology are trademarks of Sloan Company, Inc.

SloanLED Headquarters
5725 Olivas Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED Rev D 2016-04-04

 **SloanLED**[®]
Leaders in LED Technology