

# We BRIGHTEN Your BRANDS

## PosterBOX Slim

### Side illumination for shallow light boxes

- Excellent white light intensity and uniformity
- Optimal for applications as shallow as 2 inches:
  - Indoor textile prints
  - Movie posters
  - Cabinets using FlexFace®

## SPECIFICATIONS

**Part number** ..... 6500 K.....701946-6WXL P1  
5000 K.....701946-5WXL P1

**Dimensions L × W × H** ..... 4.87 in × 1.00 in × 0.61 in

**Viewing angle** ..... 15° × 43°

**LEDs per module** ..... 3

**Modules per foot** ..... 2

**Light throw** ..... 1.5 ft maximum to center of box

**Minimum cabinet depth** ..... Single-sided.....2 in  
Double-sided.....4 in

**Operating temperature** ..... -40° C to +70° C

**Protection class** ..... IP66

**Special features** ..... FanFlare lens technology  
Wire stretch feature for electrical connections

**Power per module** ..... 1.38 W

**Efficacy** ..... 87 lm/W

**Power capacity** ..... 38 modules per SloanLED 60 W 12 VDC power supply

**Fastening** ..... Peel-n-stick and mechanical

**Packaging** ..... 19 ft (38 modules) per tray, 3 trays per carton

**Color temperatures** ..... 6500 K, 5000 K

**Lumens per module** ..... 120



### Green Signage

PosterBOX™ Slim is licensed under: Patents CN200680037992.9, DE202006020673.6, NL1030161, US6932495, and US7841733; and patent applications EP06812715.8 and NL2000273. Green Signage and PosterBOX™ are trademarks of Lux et Libertas BV. SloanLED, the S logo, and Leaders in LED Technology are trademarks of Sloan Company, Inc.

SloanLED Headquarters  
5725 Olivias Park Drive • Ventura, California 93003  
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.  
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands  
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED Rev D 2016-03-22

