

We BRIGHTEN Your BRANDS

PosterBOX Slim

Side illumination for shallow light boxes

- Excellent white light intensity and uniformity
- Optimal for applications as shallow as 2 inches:
 - Indoor textile prints
 - Movie posters
 - Cabinets using FlexFace®

SPECIFICATIONS

Part number	6500 K.....701946-6WXL P1
	5000 K.....701946-5WXL P1
Dimensions L × W × H	124 mm × 26 mm × 16 mm
Viewing angle	15° × 43°
LEDs per module	3
Modules per meter	6.5
Light throw	0.5 m maximum to center of box
Minimum cabinet depth	Single-sided.....50 mm
	Double-sided.....100 mm
Operating temperature	-40° C to +70° C
Protection class	IP66
Special features	FanFlare lens technology
	Wire stretch feature for electrical connections

Power per module	1.38 W
Efficacy	87 lm/W
Power capacity	38 modules per SloanLED 60 W 12 VDC power supply
Fastening	Peel-n-stick and mechanical
Packaging	38 modules per tray, 3 trays per carton
Color temperatures	6500 K, 5000 K
Lumens per module	120



Green Signage 

PosterBOX™ Slim is licensed under: Patents CN200680037992.9, DE202006020673.6, NL1030161, US6932495, and US7841733; and patent applications EP06812715.8 and NL2000273. Green Signage and PosterBOX™ are trademarks of Lux et Libertas BV. SloanLED, the S logo, and Leaders in LED Technology are trademarks of Sloan Company, Inc.

SloanLED Headquarters
5725 Olivas Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED Rev D 2016-04-04

 **SloanLED**[®]
Leaders in LED Technology