

IMPROVED
EFFICACY

We BRIGHTEN Your BRANDS



PosterBOX Slim 2

Side illumination for shallow light boxes

- Excellent white light intensity and uniformity
- Optimal for applications as shallow as 50 mm:
 - Indoor textile prints
 - Movie posters
 - Cabinets using FlexFace®

SPECIFICATIONS

Part number	6500 K.....701946-6WXL P2
	5000 K.....701946-5WXL P2
Dimensions L x W x H	124 mm x 26 mm x 16 mm
Viewing angle	15° x 43°
LEDs per module	3
Modules per meter	6.5
Minimum box depth	Single-sided.....50 mm
	Double-sided.....100 mm
Operating temperature	-40° C to +70° C
Location rating	IP66
Special feature	FanFlare lens technology
Power per module	1.8 W
Efficacy	100 lm/W

Power capacity	30 modules per SloanLED 60 W 12 VDC power supply
Fastening	Peel-n-stick and mechanical
Packaging	38 modules per tray, 3 trays per carton
Color temperatures	6500 K, 5000 K
Lumens per module	180

1 Based on recommended module spacing.



Green Signage

PosterBOX™ Slim 2 is licensed under: Patents CN200680037992.9, DE202006020673.6, NL1030161, US6932495, and US7841733; and patent applications EP06812715.8 and NL2000273. Green Signage and PosterBOX™ are trademarks of Lux et Libertas BV. SloanLED, the S logo, and Leaders in LED Technology are trademarks of Sloan Company, Inc.

SloanLED Headquarters
5725 Olivas Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2017 SloanLED Rev B 2017-03-10

