

# We BRIGHTEN Your BRANDS



## 60C1 12 VDC Power Supply

Damp/Dry-rated 60 Watt power supply

- Universal input voltage – 100-277 VAC, 50-60 Hz input
- Auto-resetting – No fuses to replace or circuit breaker to reset. Short circuit and over-current protection circuit automatically resets when condition is corrected
- Simple secondary hook-ups – No load balancing required
- Rugged and compact

## SPECIFICATIONS

<b>Part number</b> .....	701507-60C1
<b>Dimensions L x W x H</b> .....	142 mm x 46 mm x 33 mm
<b>Nominal input voltage</b> .....	100-277 VAC, 50-60 Hz
<b>Maximum input current</b> .....	0.7 A
<b>Power output</b> .....	60 W @ 12 VDC, Class 2 output (North America only)
<b>Location rating</b> .....	Dry and damp locations
<b>Operating temperature</b> .....	-40° C to +60° C, natural convection cooling
<b>Protection class</b> .....	IP54
<b>Compatibility</b> .....	SloanLED 12 VDC products



SloanLED Headquarters  
5725 Olivas Park Drive • Ventura, California 93003  
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.  
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands  
+31 88 12 44 900 • Europe@SloanLED.com

**SloanLED.com**

© 2017 SloanLED Rev C 2017-05-24

 **SloanLED**<sup>®</sup>  
Leaders in LED Technology