

# We BRIGHTEN Your BRANDS



## Self-Contained 20 Power Supply

12 VDC 20 Watt power supply

- Auto-resetting – No fuses to replace or circuit breaker to reset. Short circuit protection automatically resets when short condition is corrected
- Simple primary hook-ups and 12 VDC Class 2 outputs
- Simple secondary hook-ups – No minimum load or load balancing required
- Rugged and compact

## SPECIFICATIONS

<b>Part number</b> .....	701680
<b>Dimensions L x W x H</b> .....	4.65 in x 1.38 in x 1.03 in
<b>Nominal input voltage</b> .....	100-240 VAC, 50-60 Hz
<b>Maximum input current</b> .....	0.55 A
<b>Power output</b> .....	20 W @ 12 VDC, Class 2 output (North America only)
<b>Location rating</b> .....	Dry and damp locations
<b>Operating temperature</b> .....	-30° C to +60° C
<b>Protection class</b> .....	IP67
<b>Compatibility</b> .....	SloanLED 12 VDC products



Self-Contained 20 is covered by U.S. and foreign patents pending and covered by one or more of the following U.S. patents issued: 6,776,504, 6,969,179, 7,192,157, 6,932,495, 7,241,031

SloanLED Headquarters  
5725 Olivias Park Drive • Ventura, California 93003  
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.  
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands  
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED Rev B 2016-04-18

 **SloanLED**<sup>®</sup>  
Leaders in LED Technology