

# We BRIGHTEN Your BRANDS

## SloanLED Prism Whites

### Reimagined LED lens technology

- Brightest lighting option in class
- Widest, most even spread of light

## SPECIFICATIONS

**Dimensions L x W x H** ..... SloanLED Prism, HO ..... 70 mm x 19 mm x 11 mm  
Mini ..... 25 mm x 18 mm x 11 mm

**LEDs per module** ..... SloanLED Prism, HO ..... 3  
Mini ..... 1

**Operating temperature** ..... SloanLED Prism, Mini ..... -40° C to +70° C  
HO ..... -40° C to +60° C

**Protection class** ..... IP66 & IP68<sup>1</sup>

**Fastening** ..... SloanLED Prism, HO ..... Peel-n-stick and mechanical  
Mini ..... Peel-n-stick



<sup>1</sup> Prism IP68 test parameters are 1.3 m submersion for 30 minutes. Do not mount in submerged application or where module will be directly exposed to prolonged flowing or dripping water.

Model	Modules per meter	Color temperature	Part number	Optimal can depth	Power per module	Lumens per module (nominal)	Efficacy	Power capacity per SloanLED 60 W 12 VDC power supply	Packaging of 5 trays per carton
SloanLED Prism	3.3/m	6500 K	701269-6WSJ2-MB	75-200 mm	1.12 W	124	111 lm/W	48 modules (14.6 m)	14.6 m (48 modules) per tray
		7100 K	701269-7WSJ1-MB						
	4.9/m	6500 K	701269-6WSJ1-MB					48 modules (9.8 m)	9.8 m (48 modules) per tray
		5700 K	701269-57SJ1-MB						
		5000 K	701269-5WSJ1-MB						
		4000 K	701269-4WSJ1-MB						
3000 K	701269-3WSJ1-MB								
Mini	7.4/m	6500 K	701269-6WMJ1-MB	50-100 mm	0.46 W	44	95 lm/W	120 modules (16.3 m)	13.0 m (96 modules) per tray
HO	2.6/m	6500 K	701269-6WHJ1-MB	127-305 mm	1.68 W	180	107 lm/W	32 modules (12.2 m)	12.2 m (32 modules) per tray
		5000 K	701269-5WHJ1-MB						

SloanLED channel letter products are covered by US and foreign patents pending and covered by one or more of the following US patents issued: 6,932,495, 7,160,140, 7,241,031, 7,520,771, 7,931,386 and European Patent No. 1756471.

SloanLED Headquarters  
5725 Olivias Park Drive • Ventura, California 93003  
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.  
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands  
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2017 SloanLED Rev C 2017-04-19



Luminous Intensity Distribution

