

Power Supply Capacity – 12 VDC products*

Maximum number of modules based on 90% of rated capacity

Channel Letter products

Model	Modules per ft/m	Watts per module	Self-Contained 20 W [701680]	60C2 60 W [701507-60C2] 60C3(D) 60 W [701507-60C3(D)] 60W3 60 W [701507-60W3]	120D1 120 W [701507-120D1]
			Power output: 20 W	Power output: 60 W	Power output: 120 W

SloanLED Prism¹² Mini

Whites (7100 K, 6500 K, 5000 K, 4000 K, 3000 K)	2.0 / 6.6	0.42	23.5 ft (7.2 m) / 47 Mods	71.0 ft (21.6 m) / 142 Mods	2 × 71.0 ft (21.6 m) / 142 Mods
Colors (Red, Green, Blue)	2.0 / 6.6	0.34	30.0 ft (9.1 m) / 60 Mods	90.0 ft (27.4 m) / 180 Mods	2 × 90.0 ft (27.4 m) / 180 Mods

SloanLED Prism

Whites (6500 K [1/ft, 3.3 m])	1.0 / 3.3	1.12	16.0 ft (4.8 m) / 16 Mods	48 ft (14.6 m) / 48 Mods	2 × 48 ft (14.6 m) / 48 Mods
Whites (7100 K, 6500 K [1.5/ft, 4.9 m], 5700 K, 5000 K, 4000 K, 3000 K)	1.5 / 4.9	1.12	10.7 ft (3.3 m) / 16 Mods	32 ft (9.8 m) / 48 Mods	2 × 32 ft (9.8 m) / 48 Mods
Colors (Red [2/ft, 6.6 m])	2.0 / 6.6	0.72	12.5 ft (3.8 m) / 25 Mods	37.5 ft (11.4 m) / 75 Mods	2 × 37.5 ft (11.4 m) / 75 Mods
Colors (Red [1.5/ft, 4.9 m], Orange, Yellow, Green, Blue)	1.5 / 4.9	0.72	16.7 ft (5.1 m) / 25 Mods	50 ft (15.2 m) / 75 Mods	2 × 50 ft (15.2 m) / 75 Mods

SloanLED Prism Mini

Whites (7100 K, 6500 K, 5000 K, 4000 K, 3000 K)	2.0 / 6.6	0.42	21.0 ft (6.4 m) / 42 Mods	64.0 ft (19.5 m) / 128 Mods	2 × 64.0 ft (19.5 m) / 128 Mods
Colors (Red, Green, Blue)	2.0 / 6.6	0.34	26.0 ft (7.9 m) / 52 Mods	79.0 ft (24.1 m) / 158 Mods	2 × 79.0 ft (24.1 m) / 158 Mods

SloanLED Prism Nano

Whites (7100 K, 6500 K, 5000 K, 4000 K, 3000 K)	7.6 / 25	0.36	6.6 ft (2.0 m) / 50 Mods	19.7 ft (6.0 m) / 150 Mods	2 × 19.7 ft (6.0 m) / 150 Mods
Colors (Red, Green, Blue)	7.6 / 25	0.12	19.7 ft (6 m) / 150 Mods	59 ft (18 m) / 450 Mods	2 × 59 ft (18 m) / 450 Mods

SloanLED Prism Enlighten[†]

Whites (7100 K, 6500 K, 5700 K, 5000 K, 4000 K, 3000 K)	1.5 / 4.9	0.75	16 ft (4.9 m) / 24 Mods	48 ft (14.6 m) / 72 Mods	2 × 48 ft (14.6 m) / 72 Mods
---	-----------	------	-------------------------	--------------------------	------------------------------

VL4

Whites (7200 K, 6500 K, 5000 K, 4000 K, 3000 K)	1.4 / 4.6	0.96	13.6 ft (4.1 m) / 19 Mods	40.0 ft (12.2 m) / 56 Mods	2 × 40.0 ft (12.2 m) / 56 Mods
Colors (Red, Green, Blue)	1.5 / 4.9	0.50	24.0 ft (7.3 m) / 36 Mods	72.0 ft (21.9 m) / 108 Mods	2 × 72.0 ft (21.9 m) / 108 Mods
High Output (6500K)	1.5 / 4.9	1.20	10.0 ft (3.0 m) / 15 Mods	30.0 ft (9.1 m) / 45 Mods	2 × 30.0 ft (9.1 m) / 45 Mods

VL4 Mini

Whites (7200 K, 6500 K, 5000 K, 4000 K, 3000 K)	2.5 / 8.2	0.36	20.0 ft (6.1 m) / 50 Mods	60.0 ft (18.3 m) / 150 Mods	2 × 60.0 ft (18.3 m) / 150 Mods
---	-----------	------	---------------------------	-----------------------------	---------------------------------

VL Plus 3

Whites (6500 K, 5000 K, 4000 K, 3000 K)	1.4 / 4.6	1.04	12.1 ft (3.7 m) / 17 Mods	37.1 ft (11.3 m) / 52 Mods	2 × 37.1 ft (11.3 m) / 52 Mods
Colors (Red)	1.4 / 4.6	0.63	20.7 ft (6.3 m) / 29 Mods	61.4 ft (18.7 m) / 86 Mods	2 × 61.4 ft (18.7 m) / 86 Mods
Colors (Green, Blue)	1.4 / 4.6	0.54	23.6 ft (7.2 m) / 33 Mods	71.4 ft (21.8 m) / 100 Mods	2 × 71.4 ft (21.8 m) / 100 Mods
High Output (6500K, 5000 K)	1.4 / 4.6	1.27	10.0 ft (3.0 m) / 14 mods	30.0 ft (9.1 m) / 42 mods	2 × 30.0 ft (9.1 m) / 42 mods

VL Plus 3 Mini

Whites (6500 K, 5000 K, 4000 K)	2.0 / 6.7	0.49	18 ft (5.5 m) / 36 Mods	55.0 ft (16.8 m) / 110 Mods	2 × 55.0 ft (16.8 m) / 110 Mods
---------------------------------	-----------	------	-------------------------	-----------------------------	---------------------------------

NOTE: When mixing modules of different sizes/colors or various products on the same power supply, simply add all the power requirements for the respective footages of each product. Then choose appropriate power supplies to provide adequate power output. The actual number of power supplies needed may vary based on how the materials are distributed across the project.

* Configured for Class 2 Output.

† No longer available.

Power Supply Capacity – 12 VDC products*

Maximum number of modules based on 90% of rated capacity

Channel Letter products

Model	Modules per ft/m	Watts per module	Self-Contained 20 W [701680]	60C2 60 W [701507-60C2] 60C3(D) 60 W [701507-60C3(D)] 60W3 60 W [701507-60W3]	120D1 120 W [701507-120D1]
			Power output: 20 W	Power output: 60 W	Power output: 120 W

V180					
Large	2.0 / 6.6	1.20	7.5 ft (2.3 m) / 15 Mods	22.5 ft (6.9 m) / 45 Mods	2 × 22.5 ft (6.9 m) / 45 Mods
Standard†	2.5 / 8	0.55	12.8 ft (3.9 m) / 32 Mods	39.2 ft (11.9 m) / 98 Mods	2 × 39.2 ft (11.9 m) / 98 Mods
Mini	2.5 / 8	0.31	22.8 ft (6.9 m) / 57 Mods	69.0 ft (21.0 m) / 173 Mods	2 × 69.0 ft (21.0 m) / 173 Mods
HB Mini	2.0 / 6.6	0.59	15 ft (4.6 m) / 30 Mods	46 ft (14.0 m) / 92 Mods	2 × 46 ft (14.0 m) / 92 Mods

VL Plus Series†					
VL Plus Long (Red)	2.0 / 6.5	0.36	25 ft (7.6 m) / 50 Mods	75 ft (23 m) / 150 Mods	2 × 75 ft (23 m) / 150 Mods
VL Plus Short (Red, Yellow, Orange)	2.5 / 8	0.29	25 ft (7.6 m) / 62 Mods	74.8 ft (22.8 m) / 187 Mods	2 × 74.8 ft (22.8 m) / 187 Mods
VL Plus Short (Blue, Green)	2.5 / 8	0.36	20 ft (6.1 m) / 50 Mods	60 ft (18.3 m) / 150 Mods	2 × 60 ft (18.3 m) / 150 Mods
VL Plus 2 Long (White)	2.0 / 6.5	0.54	16.7 ft (5.1 m) / 33 Mods	50 ft (15.2 m) / 100 Mods	2 × 50 ft (15.2 m) / 100 Mods
VL Plus 2 Short/HB (White)	2.5 / 8	0.54	13.3 ft (4.1 m) / 33 Mods	40 ft (12.2 m) / 100 Mods	2 × 40 ft (12.2 m) / 100 Mods
VL Plus 2 Mini (White)	2.5 / 8	0.54	10.7 ft (3.3 m) / 43 Mods	32 ft (9.8 m) / 128 Mods	2 × 32 ft (9.8 m) / 128 Mods

BendLUX					
BendLUX	2 ft (0.6 m) strips	4.2 W per strip	8 ft (2.5 m) / 4 Strips	25 ft (8 m) / 12.5 Strips	2 × 25 ft (8 m) / 12.5 Strips

SloanLED FlexTAPE					
SloanLED FlexTAPE White (6500 K, 5000 K, 3500 K)	18 / 60	1.4 W per ft / 4.6 W per m	12.8 ft (3.9 m)	38.4 ft (11.7 m)	2 × 38.4 ft (11.7 m)
SloanLED FlexTAPE Red	18 / 60	1.1 W per ft / 3.6 W per m	16.4 ft (5 m)	49.2 ft (15.0 m)	2 × 49.2 ft (15.0 m)

Sign Cabinet/Box products

Model	Modules per ft/m	Watts per module	Self-Contained 20 W [701680]	60C2 60 W [701507-60C2] 60C3(D) 60 W [701507-60C3(D)] 60W3 60 W [701507-60W3]	120D1 120 W [701507-120D1]
			Power output: 20 W	Power output: 60 W	Power output: 120 W

PosterBOX Series					
PosterBOX Slim 2 (Gen 2)	1.4 / 4.6	1.68	7.1 ft (2.2 m) / 10 Mods	22.7 ft (6.9 m) / 32 Mods	22.7 ft (6.9 m) (32 Mods × 2)
PosterBOX Slim	2.0 / 6.5	1.38	6 ft (1.8 m) / 12 Mods	19 ft (5.8 m) / 38 Mods	38 ft (11.6 m) (38 Mods × 2)
PosterBOX	1.6 / N/A‡	6.70	2 Mods	8 Mods	8 Mods × 2
PosterBOX Mini	1.6 / 5.31	6.70	15 Mods	45 Mods	45 Mods × 2

SignBOX II					
Single-sided	3.0 / 10.0	0.90	6.6 ft (2.0 m) / 20 Mods	20 ft (6.1 m) / 60 Mods	40 ft (12.2 m) (60 Mods × 2)
Double-sided	3.0 / 10.0	1.80	3.3 ft (1.0 m) / 10 Mods	10 ft (3.0 m) / 30 Mods	20 ft (6.1 m) (30 Mods × 2)

NOTE: When mixing modules of different sizes/colors or various products on the same power supply, simply add all the power requirements for the respective footages of each product. Then choose appropriate power supplies to provide adequate power output. The actual number of power supplies needed may vary based on how the materials are distributed across the project.

* Configured for Class 2 Output.
 † No longer available.
 ‡ Contact Customer Service for details.

Power Supply Capacity – 12 VDC products*

Maximum number of modules based on 90% of rated capacity

Linear Lighting products

Model	Power used per fixture in Watts	Self-Contained 20 W [701680]	60C2 60 W [701507-60C2] 60C3(D) 60 W [701507-60C3(D)] 60W3 60 W [701507-60W3]	120D1 120 W [701507-120D1]
		Power output: 20 W	Power output: 60 W	Power output: 120 W

SlimLINER

Model	Power used per fixture	2 fixtures	6 fixtures	6 fixtures × 2
SlimLINER	9.02 W			

Border Tubing & Accent products

Model	Power used per ft/m in Watts	Self-Contained 20 W [701680]	60C2 60 W [701507-60C2] 60C3(D) 60 W [701507-60C3(D)] 60W3 60 W [701507-60W3]	120D1 120 W [701507-120D1]
		Power output: 20 W	Power output: 60 W	Power output: 120 W

ColorLINE

All colors	2.30 / 9.2	Max. 8 ft / 2.4 m	Max. 24 ft / 7.3 m	Max. 24 ft / 7.3 × 2

FlexiBRITE

All colors	2.80 / 7.5	Max. 6 ft / 2 m	Max. 20 ft / 6 m	Max. 20 ft / 6 m × 2

NOTE: When mixing modules of different sizes/colors or various products on the same power supply, simply add all the power requirements for the respective footages of each product. Then choose appropriate power supplies to provide adequate power output. The actual number of power supplies needed may vary based on how the materials are distributed across the project.

* Configured for Class 2 Output.

Power Supply Capacity – 24 VDC products

Maximum number of modules based on 90% of rated capacity

Channel Letter Products

Model	Modules per ft/m	Watts per module	60S1(D) Power Supply [701895-60S1(D)]	24 VDC Power Supply [701895-24C1] 24S1 100 W Power Supply [701895-24S1] 24S2(D) 100 W Power Supply [701895-24S2(D)]	300T1 Power Supply [701895-300T1]
			Power output: 60 W	Power output: 100 W	Power output: 300 W

SloanLED Prism²⁴

Whites (7100 K, 6500 K, 5000 K, 4000 K, 3000 K)	1.2 / 3.9	0.86	51.7 ft (15.8 m)/62 mods	86.7 ft (26.4 m)/104 mods	3 × 86.7 ft (26.4 m)/104 mods
Colors (Red)	1.5 / 4.9	0.43	83.4 ft (25.4 m)/125 mods	138.7 ft (42.3 m)/208 mods	3 × 136.0 ft (41.5 m)/340 mods
Colors (Green)	1.5 / 4.9	0.54	66.6 ft (20.3 m)/100 mods	111.3 ft (33.9 m)/167 mods	3 × 111.3 ft (33.9 m)/167 mods
Colors (Blue)	1.5 / 4.9	0.59	60.6 ft (18.5 m)/91 mods	101.3 ft (30.9 m)/152 mods	3 × 101.3 ft (30.9 m)/152 mods
High Output (6500 K, 5000 K)	0.8 / 2.6	1.20	56.3 ft (17.2 m)/45 mods	93.8 ft (28.6 m)/75 mods	3 × 93.8 ft (28.6 m)/75 mods

SloanLED Prism²⁴ Mini

Whites (7100 K, 6500 K, 5000 K, 4000 K, 3000 K)	2.5 / 8.2	0.40	54.0 ft (16.5 m)/135 mods	90.0 ft (27.4 m)/225 mods	3 × 90.0 ft (27.4 m)/225 mods
Colors (Red, Green)	2.5 / 8.2	0.26	81.6 ft (24.9 m)/204 mods	136.0 ft (41.5 m)/340 mods	3 × 136.0 ft (41.5 m)/340 mods
Colors (Blue)	2.5 / 8.2	0.44	46.8 ft (14.3 m)/117 mods	81.6 ft (24.9 m)/204 mods	3 × 81.6 ft (24.9 m)/204 mods

SloanLED Prism²⁴ LP

Whites (7100 K, 6500 K, 5000 K, 4000 K, 3000 K)	1.5 / 4.9	0.43	83.4 ft (25.4 m)/125 mods	138.7 ft (42.3 m)/208 mods	3 × 138.7 ft (42.3 m)/208 mods
---	-----------	------	---------------------------	----------------------------	--------------------------------

VL4 Super High Output

White (6500 K)	0.65 / 2.13	1.42	92.3 ft (28.1 m) / 60 mods	92.3 ft (28.1 m) / 60 mods	3 × 92.3 ft (28.1 m) / 60 mods
----------------	-------------	------	----------------------------	----------------------------	--------------------------------

NOTE: When mixing modules of different sizes/colors or various products on the same power supply, simply add all the power requirements for the respective footages of each product. Then choose appropriate power supplies to provide adequate power output. The actual number of power supplies needed may vary based on how the materials are distributed across the project.

Power Supply Capacity – 24 VDC products

Maximum number of modules based on 90% of rated capacity

Sign Cabinet/Box products

Model	Watts per assembly	24 VDC Power Supply [701895-24C1] 24S1 100 W Power Supply [701895-24S1] 24S2(D) 100 W Power Supply [701895-24S2(D)]		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W

PosterBOX 3 Maximum units per power supply[§]

Model	Watts per assembly	7 units max.	12 units max.	3 × 12 units max.
PosterBOX 3 Short	7.2	7 units max.	12 units max.	3 × 12 units max.
PosterBOX 3 Long	14.0	3 units max.	6 units max.	3 × 6 units max.

Model	Watts per assembly	24 VDC Power Supply [701895-24C1] 24S1 100 W Power Supply [701895-24S1] 24S2(D) 100 W Power Supply [701895-24S2(D)]		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W

PosterBOX ID Maximum units per power supply[§]

Model	Watts per assembly	7 units max.	12 units max.	3 × 12 units max.
PosterBOX ID Short	7.2	7 units max.	12 units max.	3 × 12 units max.
PosterBOX ID Long	14.0	3 units max.	6 units max.	3 × 6 units max.

Model	Power used per ft/m in Watts	24 VDC Power Supply [701895-24C1] 24S1 100 W Power Supply [701895-24S1] 24S2(D) 100 W Power Supply [701895-24S2(D)]		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W

SignBOX 3

Model	Watts per assembly	7 units max.	12 units max.	3 × 12 units max.
Max. SignBOX 3 single-sided modules, or one side of double-sided	1.92 / 6.3	28	48	3 × 48
Maximum SignBOX 3 Double-sided modules, both sides	3.84 / 12.6	14	24	3 × 24

Model	Watts per module	24 VDC Power Supply [701895-24C1] 24S1 100 W Power Supply [701895-24S1] 24S2(D) 100 W Power Supply [701895-24S2(D)]		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W

SloanLED BrightLINE Maximum feet (meters) / LED Strips

Model	Watts per assembly	4.9 ft (1.5 m) / 10 strips	8.9 ft (2.7 m) / 18 strips	3 × 8.9 ft (2.7 m) / 18 strips
6500 K	4.8	4.9 ft (1.5 m) / 10 strips	8.9 ft (2.7 m) / 18 strips	3 × 8.9 ft (2.7 m) / 18 strips

SloanLED BrightLINE Short Maximum feet (meters) / LED Strips

Model	Watts per assembly	16.3 ft (5.0 m) / 33 strips	27.6 ft (8.4 m) / 56 strips	3 × 27.6 ft (8.4 m) / 56 strips
6500 K	1.6	16.3 ft (5.0 m) / 33 strips	27.6 ft (8.4 m) / 56 strips	3 × 27.6 ft (8.4 m) / 56 strips

NOTE: When mixing modules of different sizes/colors or various products on the same power supply, simply add all the power requirements for the respective footages of each product. Then choose appropriate power supplies to provide adequate power output. The actual number of power supplies needed may vary based on how the materials are distributed across the project.

* If length of part is unknown, it can be found in product part number: X=CCT, YYY = Length in inches (701972-[X]WP[D,S][YYY]3).

† If length of part is unknown, it can be found in product part number: X=CCT, YYY = Length in inches (701972-[X]W24P[D,S][YYY]1).

‡ Any combination thereof not to exceed power rating of power supply.

§ Combination of units must not exceed maximum power supply output.

Length	Watts per assembly (single-sided/double-sided)	24 VDC Power Supply [701895-24C1] 24S1 100 W Power Supply [701895-24S1] 24S2(D) 100 W Power Supply [701895-24S2(D)]		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W

SloanLED PrismBEAM[‡], 24 VDC (701972-[X]WP[D,S][YYY]3)

Length	Watts per assembly (single-sided/double-sided)	Maximum lamps per power supply (single-sided/double-sided)		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W
18 in (0.46 m)	3.1 / 6.2	28 / 14	28 / 14	3 × 28 / 14
24 in (0.61 m)	4.7 / 9.4	19 / 9	19 / 9	3 × 19 / 9
30 in (0.76 m)	4.7 / 9.4	19 / 9	19 / 9	3 × 19 / 9
36 in (0.91 m)	6.2 / 12.5	14 / 7	14 / 7	3 × 14 / 7
42 in (1.07 m)	7.8 / 15.6	11 / 5	11 / 5	3 × 11 / 5
48 in (1.22 m)	9.4 / 18.7	9 / 4	9 / 4	3 × 9 / 4
60 in (1.52 m)	10.9 / 21.8	8 / 4	8 / 4	3 × 8 / 4
64 in (1.63 m)	12.5 / 25.0	7 / 3	7 / 3	3 × 7 / 3
72 in (1.83 m)	14.0 / 28.1	6 / 3	6 / 3	3 × 6 / 3
84 in (2.13 m)	15.6 / 31.2	5 / 2	5 / 2	3 × 5 / 2
96 in (2.44 m)	18.7 / 37.4	4 / 2	4 / 2	3 × 4 / 2
108 in (2.74 m)	20.3 / 40.6	4 / 2	4 / 2	3 × 4 / 2
117 in (2.97 m)	21.8 / 43.7	4 / 2	4 / 2	3 × 4 / 2
120 in (3.05 m)	21.8 / 43.7	4 / 2	4 / 2	3 × 4 / 2

Length	Watts per assembly (single-sided/double-sided)	24 VDC Power Supply [701895-24C1] 24S1 100 W Power Supply [701895-24S1] 24S2(D) 100 W Power Supply [701895-24S2(D)]		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W

SloanLED PrismBEAM^{‡†}, (701972-[X]W24P[D,S][YYY]1)

Length	Watts per assembly (single-sided/double-sided)	Maximum lamps per power supply (single-sided/double-sided)		
		60S1(D) Power Supply [701895-60S1(D)] Power output: 60 W	300T1 Power Supply [701895-300T1] Power output: 100 W	300T1 Power Supply [701895-300T1] Power output: 300 W
18 in (0.46 m)	2.5 / 5.1	21 / 10	28 / 14	3 × 36 / 18
24 in (0.61 m)	2.5 / 5.1	21 / 10	19 / 9	3 × 36 / 18
30 in (0.76 m)	3.8 / 7.6	14 / 7	19 / 9	3 × 24 / 12
36 in (0.91 m)	3.8 / 7.6	14 / 7	14 / 7	3 × 24 / 12
42 in (1.07 m)	5.1 / 10.2	10 / 5	11 / 5	3 × 18 / 9
48 in (1.22 m)	6.4 / 12.7	8 / 4	9 / 4	3 × 14 / 7
60 in (1.52 m)	7.6 / 15.3	7 / 3	8 / 4	3 × 12 / 6
64 in (1.63 m)	7.6 / 15.3	7 / 3	7 / 3	3 × 12 / 6
72 in (1.83 m)	8.9 / 17.8	6 / 3	6 / 3	3 × 10 / 5
84 in (2.13 m)	10.2 / 20.4	5 / 2	5 / 2	3 × 9 / 4
96 in (2.44 m)	11.4 / 22.9	4 / 2	4 / 2	3 × 8 / 4
108 in (2.74 m)	14.0 / 28.0	3 / 1	4 / 2	3 × 6 / 3
117 in (2.97 m)	15.3 / 30.5	3 / 1	4 / 2	3 × 6 / 3
120 in (3.05 m)	15.3 / 30.5	3 / 1	4 / 2	3 × 6 / 3

Power Supply Capacity – 24 VDC products

Maximum number of modules based on 90% of rated capacity

Border Tubing & Accent products

Model	Watts per assembly	6051(D) Power Supply [701895-6051(D)]	24 VDC Power Supply [701895-24C1] 2451 100 W Power Supply [701895-2451] 2452(D) 100 W Power Supply [701895-2452(D)]	300T1 Power Supply [701895-300T1]
		Power output: 60 W	Power output: 100 W	Power output: 300 W

LEDStripe

All colors*	1.5 W/ft (5 W/m)	36 ft / 11 m	Two legs 30 ft / 9.04 m each*	3 × two legs 30 ft / 9.04 m each*
-------------	---------------------	--------------	----------------------------------	--------------------------------------

* If more than two parallel legs are used, check output voltage and current of power supply: Current ≤ 4.0 A, Voltage ≥ 23.3 VDC.

Linear Lighting products

Model	Watts per assembly	24 VDC Power Supply [701895-24C1] 2451 100 W Power Supply [701895-2451] 2452(D) 100 W Power Supply [701895-2452(D)]
		Power output: 100 W

HighLINER 3

HighLINER 3	3.6 W/ft (11.8 W/m)	Max. 24 ft / 7 m
-------------	------------------------	------------------

Model	Watts per assembly	24 VDC Power Supply [701895-24C1] 2451 100 W Power Supply [701895-2451] 2452(D) 100 W Power Supply [701895-2452(D)]
		Power output: 100 W

HighLINER 2

HighLINER 2	3.6 W/ft (11.8 W/m)	Max. 24 ft / 7 m
-------------	------------------------	------------------

Model	Watts per assembly	6051(D) Power Supply [701895-6051(D)]	24 VDC Power Supply [701895-24C1] 2451 100 W Power Supply [701895-2451] 2452(D) 100 W Power Supply [701895-2452(D)]	300T1 Power Supply [701895-300T1]
		Power output: 60 W	Power output: 100 W	Power output: 300 W

SloanLED LEDBlade, 24 VDC

SloanLED LEDBlade	30	One (1), 5-ft (1.5-m) SloanLED LEDBlade section	Three (3), 5-ft (1.5-m) SloanLED LEDBlade sections	3 × three (3), 5-ft (1.5-m) SloanLED LEDBlade sections
-------------------	----	---	--	---

SloanLED Headquarters
5725 Olivas Park Drive, Ventura, CA, USA
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Argonstraat 110, 2718 SN Zoetermeer, NL
+31 88 12 44 900 • europe@SloanLED.com



SloanLED.com

© 2022 SloanLED Rev W 2022-01-17

Specifications subject to change without notice.

