

BendLUX

Low-profile, flexible strip lighting

Specifications

- Part number 701960-6WS241
- Dimensions L x W x H 610 mm x 8 mm x 3 mm
- Viewing angle 120°
- LEDs per section 3
- Lumens per strip 365
- Color temperature (nominal) 6500 K
- Minimum radial bend radius 25 mm
- Operating temperature -40° C to +70° C
- Special feature "Snap-n-Stretch" 45 mm sections for easy flat bends and connections
- Power 0.3 W per section, 4.2 W per strip
- Efficacy 85 lm/W
- Fastening Peel-n-stick
- Packaging 12 strips per box



BendLUX is covered by patents pending.

Power Supply Capacity

12 VDC Power supply*	BendLUX
20 W Power supply	2.4 m
25 W Power supply (EU/ROW ONLY)	3.2 m
30 W Power supply (EU/ROW ONLY)	3.8 m
60 W Power supply	7.6 m
2 x 60 W Power supply	2 x 7.6 m
2 x 75 W Power supply (EU/ROW ONLY)	2 x 9.5 m
Watts per meter	6.9 W

* Configured for Class 2 Output.

Density Guidelines

Size	Module color	Can Depth	Modules per meter	Milimeters on center standard face	Milimeters on center dark vinyl	Milimeters on center perforated vinyl	Watts per module	Modules per M ² standard face	Modules per M ² dark vinyl
N/A	White (6500 K)	30	22	30	Test	Test	0.3 (per segment)	733.3	Test

These guidelines are intended to provide only an approximation of BendLUX product required for your sign, assuming an optimal balance of performance and cost. SloanLED is not responsible for the actual results based on the use of these guidelines.

Notes:

- Test results based on Evonik WN070 3 mm acrylic, 30% translucency.
- It is recommended that you first test LED density in sample letter/cabinet to evaluate brightness, uniformity and color.
- Should you have questions or require assistance in testing, please contact your SloanLED customer service representative.
- > Symbol represents greater than. < Symbol represents less than. ≥ Symbol represents greater than or equal to.
- For multiple rows, calculate half of the row spacing given from the table and start first row offset that distance from return.
- Products can be used in can depths deeper or shallower than listed above, but testing is recommended.
- Maximum single row coverage is (Milimeters on center with standard face) x 1.25.

SloanLED Headquarters

5725 Olivas Park Drive, Ventura, CA, USA
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.

Argonstraat 110, 2718 SN Zoetermeer, NL
+31 88 12 44 900 • europe@SloanLED.com



SloanLED.com



Visit product page for details.