

PosterBOX 3

Large, shallow fabric-faced light box illumination

Specifications

Part number	Short	701946-6WSRP1
	Long	701946-6WLRP1
Dimensions L x W x H	Short	251 mm x 38 mm x 19 mm (9.89 in x 1.50 in x 0.74 in)
	Long	501 mm x 38 mm x 19 mm (19.73 in x 1.50 in x 0.74 in)
Viewing angle	12.2° x 44.8° illumination	
LEDs per assembly	Short	3
	Long	6
Color temperature (nominal)	6500 K	
Minimum cabinet depth	Single-sided	75 mm (3 in)
	Double-sided	100 mm (4 in)
Operating temperature	-40° C to +70° C	
Protection class	IP66	
Life rating	>60,000 hours	
Power per module	Short	7.2 W
	Long	14.0 W
Efficacy	Short	118 lm/W
	Long	121 lm/W
Power capacity*	Per SloanLED 100 W 24 VDC power supply	
	Short	12 modules
	Long	6 modules
Fastening	Mechanical fasteners, Peel-n-stick (optional)	
Packaging	6 assemblies per tray, 5 trays per carton	
Lumens per assembly	Short	850
	Long	1700



Power Supply Capacity*

Item description	PosterBOX 3 Short	PosterBOX 3 Long
100 W Power Supply	3 m (10 ft) / 12 Mods	3 m (10 ft) / 6 Mods
40 W Power Supply	1.25 m (4.1 ft) / 5 Mods	0.9 m (3 ft) / 2 Mods
Watts per assembly	7.2	14.0

* Any combination thereof not to exceed power rating of power supply.



SloanLED Headquarters
5725 Olivias Park Drive, Ventura, CA, USA
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Argonstraat 110, 2718 SN Zoetermeer, NL
+31 88 12 44 900 • europe@SloanLED.com



SloanLED.com



Visit product page for details.