

Universal Primary Wire Enclosure

Primary connection housing

- Convenient primary connection housing eliminates need to enclose entire power supply, saving time and money
- Features four (4) 0.5" (12.7 mm) trade size knockouts
- UL approved for primary wire protection
- Easy access cover for wire connection
- Suitable for dry and damp locations

Specifications

Part number	Gen 2	403008
	Gen 1	402218
Dimensions L x W x H	Gen 2	4.04 in x 1.72 in x 1.20 in (103 mm x 44 mm x 30 mm)
	Gen 1	4.04 in x 1.65 in x 1.22 in (103 mm x 42 mm x 31 mm)
Weight		0.25 lbs (0.10 kg)
Material		Galvanized steel
Finish		Matte white powder coat
Location rating		Dry and damp locations
Knockouts		Four (4) 0.5" (12.7 mm) trade size knockouts
Packaging		50 pieces per box

Compatibility

Item description (Part number)	Power output	Compatibility
12 VDC Power supplies		
60C1 60 W [701507-60C1]*	60 W	Gen 1 & 2
60C2 60 W [701507-60C2]	60 W	Gen 1 & 2
60C3(D) 60 W [701507-60C3(D)]	60 W	Gen 2
120D1 120 W [701507-120D1]	120 W	Gen 1 & 2
24 VDC Power supplies		
24 VDC 100 W [701936]*	100 W	Gen 1 & 2
60S1(D) 60 W [701895-60S1(D)]	60 W	Gen 2

* No longer available.



SloanLED Headquarters
5725 Olivas Park Drive, Ventura, CA, USA
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Argonstraat 110, 2718 SN Zoetermeer, NL
+31 88 12 44 900 • europe@SloanLED.com



SloanLED.com

© 2021 SloanLED Rev C 2021-12-14

Specifications subject to change without notice.



Gen 2
P/N: 403008



Gen 1
P/N: 402218

